

CLAD BOY

VACUUM LIFTING DEVICE FOR ROOF AND WALL PANELS



Configuration for roof panels



LIFTING EYE

INDICATION
Battery charging level

SOLID GRIPS

STORAGE BOX
Connection cable
battery charger

VACUUM GAUGE
Red-green indication

WATER SEPARATOR

QUICK COUPLINGS
To connect vacuum hoses

LOCKING PIN
To lock the main traverse
in both end positions

SUCTION PADS
With exchangeable seals

MAIN TRAVERSE
90° rotatable

CONTROL
Suction and release
with safety latch

CASING
For the electric components

POSSIBILITIES

With the option of various suction pads and extension kits, the machine is uniquely flexible and versatile and can be used for many applications such as:

- Horizontal wall panels
- Vertical wall panels
- Flat or inclined roof panels

The standard suction pads are suitable for all commonly used sandwich roof and wall panels. For other profiles such as corrugated and roof tile profile, special suction pads are available.

SAFETY FEATURES

- Clear audible low vacuum warning
- Large vacuum buffer tank
- Low battery warning
- Secondary safety device

SPECIFICATION

- Lifting capacity: dictated by suction pads in use up to a maximum machine capacity of max. 880lbs (400kgs)
- Machine weight: dictated by lifting configuration but minimum self weight is 275lbs (125Kg).



EASY TO TRANSPORT

COMPACT AND DURABLE POWERED BY INTERNAL RE-CHARGEABLE BATTERY

